

# UNWIND / REWIND BELTS



## Nycor Belting Program

Shingle Belting is pleased to offer its full line of Nycor nylon core belting products to the paper converting industry. Our Shingle nylon core belting products have been designed and built to meet the specific requirements of paper converters across the U.S. For unwind / rewinds we offer the following belt types:

Belt Style	Composition	Application
SG35A Nycor	2.8 mm High Tensile Rubber / Textile nylon core	Unwind / Rewind
SG333 Nycor	3.0 mm High Tensile Rubber / Rubber nylon core	Unwind / Rewind
SG3K5 Nycor	4.0 mm High Tensile Synthetic Leather / Rubber nylon core	Unwind / Rewind

*\* other unwind / rewind belts are highlighted in green on the back of this brochure*

Extend your unwind / rewind belt life with Shingle Belting's:

- Abrasion resistant SG covers
- Custom engineered splice materials
- Special core winder lap

See the back of this brochure for our full line of problem solving nylon core belts

# Nycor Specifications

LEATHER NYCOR					
Type	Top Cover	Pulley Cover	Approx. Thickness (in.)	Min. Pulley (in.)	Pull for 1% (lbs/in)
L-20	Textile	Leather	0.105	1.5	30
L-30	"	"	0.115	2.0	45
L-40	"	"	0.125	2.5	60
L-50	"	"	0.135	4.0	75
L-70	"	"	0.155	6.0	105
L-105	"	"	0.185	10.0	150
L-140	"	"	0.225	18.0	210
L-180	"	"	0.265	26.0	270
L-210	"	"	0.300	30.0	315
2L-20	Leather	"	0.155	1.5	30
2L-30	"	"	0.165	2.0	45
2L-40	"	"	0.175	2.5	60
2L-50	"	"	0.185	4.0	75
2L-70	"	"	0.205	6.0	105
2L-105	"	"	0.240	10.0	150
2L-140	"	"	0.275	18.0	210
2L-180	"	"	0.315	26.0	270
K-20	Textile	Synthetic	0.100	1.5	30
K-30	"	"	0.110	2.0	45
K-50	"	"	0.130	4.0	75
K-70	"	"	0.150	6.0	105
2K-20	Synthetic	"	0.170	1.5	30
2K-30	"	"	0.180	2.0	45
2K-50	"	"	0.200	4.0	75
2K-70	"	"	0.220	6.0	105

RUBBER NYCOR					
Type	Top Cover	Pulley Cover	Approx. Thickness (in.)	Min. Pulley (in.)	Pull for 1% (lbs/in)
Tex 1.1	"	"	0.045	1.0	12
SG 1A	Rubber	Anti-Static	0.039	0.6	20
SG 11A	"	"	0.060	1.0	30
SG 155	"	Rubber	0.120	1.2	30
SG 2TT	Textile	Textile	0.052	1.5	30
SG 21A	Rubber	Anti-Static	0.060	1.5	30
SG 211	"	Rubber	0.076	1.5	30
SG 25A	"	Anti-Static	0.100	2.0	30
SG 31A	"	"	0.074	2.0	45
SG 311	"	Rubber	0.086	2.0	45
SG 35A	"	Anti-Static	0.110	2.0	45
SG 355	"	Rubber	0.158	2.5	45
SG 388	"	"	0.197	2.5	45
SG 39A	"	Anti-Static	0.150	2.5	45
SG 399	"	Rubber	0.236	2.5	45
SG 411	"	"	0.096	2.5	60
SG 45A	"	Anti-Static	0.120	3.0	60
SG 511	"	Rubber	0.106	4.0	75
SG 515	"	"	0.137	4.5	75
SG 555	"	"	0.178	4.5	75
SG 60A	"	Anti-Static	0.235	6.0	45
SG 711	"	Rubber	0.126	6.0	105
SG 755	"	"	0.198	6.0	105
SG 10555	"	"	0.224	10.0	150
SG 14015	"	"	0.222	18.0	210
SG 18015	"	"	0.262	26.0	270

Shingle Belting  
 420 Drew Court  
 King of Prussia, PA 19406  
 Phone: 800-345-6294  
 Fax: 610-825-0315  
[www.shinglebelting.com](http://www.shinglebelting.com)

